

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS

I set Maple post, $4\frac{1}{2}$ feet long, 4 ins. square, 24 ins. in the ground at the point of intersection for the closing corner to secs. 27 and 28, marked T. 22 S., S. 27 on the East, R. 9 W., S. 28 on the West, and C. C. on the North faces with 1 groove on the S. and 3 grooves on the E. sides, from which,

A Fir, 24 ins. diam., bears N.9°E., 100 lks. dist.

Marked T. 22 S., R. 9 W., S. 27 B. T.

A Fir, 40 ins. diam., bears S.30°E., 26 lks. dist.

Marked C. C. T. 22 S., R. 9 W., S. 27-28 B. T.

A Fir, 20 ins. diam., bears N.49°W., 104 lks. dist.

Marked T. 22 S., R. 9 W., S. 28 B. T.

Land, broken and mountainous. 74.40 chs.

Soil, second and third rate.

Timber, Fir, Hemlock and Maple.

Undergrowth, dense, Hazel, Thimble and Salmonberry,

Willow and Sal&berry. 74.40 chs.

October 27, 1894.

Commenced at the corner to secs. 16, 17 20 and 21, which

I re-established, as follows:

Set an Alder post, $4\frac{1}{2}$ feet long, 4 ins. square, 24 ins.

in the ground on hillside sloping North, marked

T. 22 S. S. 16 on the NE., R. 9 W., S. 21 on the SE., S.

S. 20 on the SW, and S. 17 on the NW. faces with 3 on S. & 4

notches on the E. edges, from which,

A Fir, 24 ins. diam., bears S.45°W., 34 lks. dist.

Marked T. 22 S., R. 9 W., S. 20 B. T.

A Fir, 60 ins. diam., bears N.40°W., 55 lks. dist.

Marked T. 22 S., R. 9 W., S. 17 B. T.

I marked,