

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS		
	A Maple, 6 ins. diam., bears N.41*E., 37 lks. dist. Marked T. 22 S., R. 9 W., S. S. 16 B. T.	
	An Alder, 6 ins. diam., bears S.17*E., 33 lks. dist. Marked T. 22 S., R. 9 W., S. 21 B. T.	
	The bearing trees agrees only in part with notes furnished me by the U. S. Surveyor General.	
	Thence, I run, S.0*01*E., between secs. 20 and 21. Va. 19*30*E.	
12.30	A creek, 1 lk. wide, Course NE.	
22.70	A creek, 1 lk. wide, Course NE.	
40.00	Set Fir post, 4½ feet long, 4 ins. square, 24 ins. in the ground, on hillside sloping NE. for ¼ sec. corner, marked ¼ S. on the W. face, from which, A Fir, 16 ins. diam., bears S.54*E., 114 lks. dist. Marked ¼ S. B. T. A Fir, 36 ins. diam., bears S.27*W., 28 lks. dist. Marked ¼ S. B. T.	
45.00	Top of ridge, Course SE. and NW. Descend.	+ 200
62.50	A creek, 1 lk. wide, Course SW. Ascend.	- 200
70.00	Spur, Course SW. Descend.	+ 100
74.20	A creek, 1 lk. wide, Course SW.	
78.00	Pass over spur.	
80.00	Set Maple post, 4½ feet long, 4 ins. square, 24 ins. in ground on steep hillside sloping SW for corner to secs. 20, 21, 28 and 29, marked T. 22 S., S. 21 on the NE. R. 9 W., S. 28 on the SE., S. 29 on the SW. and S. 20 on the NW. faces with 2 notches on the S. and 4 notches on the edges, from which,	