

Subdivisions of T. 22 S., R. 9 W.

CHAINS

74.38 Intersected E. and W. line, 590 lks., S. 89°42'E. of the corner to secs. 32 and 33, which is a post, 30 ins. above ground, 3 ins. square, firmly set, and marked T. 22 S., S. 28 on the NE., R. 9 W. S. 33 on the SE., S. 32 on the SW., and S. 29 on the NW. faces, with 1 notch on the S., and 4 notches on the E. edge.

I obliterated marks on the NE. and NW. faces and added T. 22 S. on the SW. face, from which,

A Fir, 20 ins. diam., bears N. 85°E., 52 lks. dist.
Marked T. 22 S., R. 9 W., S. 28 B. T.

A Fir, 30 ins. diam., bears S. 25°E., 60 lks. dist.
Marked T. 22 S., R. 9 W., S. 33 B. T.

A Fir, 48 ins. diam., bears S. 20°W., 24 lks. dist.
Marked T. 22 S., R. 9 W., S. 32 B. T.

A Fir, 18 ins. diam., bears N. 36°W., 37 lks. dist.
Marked T. 22 S., R. 9 W., S. 29 B. T.

Agreeing in part with notes furnished me by the U. S. Surveyor General. I destroyed the marks on the bearing tree in sec. 29.

Set Fir post, 4½ feet long, 4 ins. square, 24 ins. in the ground at the point of intersection, on steep hillside sloping SW. for closing corner to secs. 28 and 29, marked C. C. on the North, T. 22 S. S. 28 on the E., and R. 9 W., S. 29 on the West side, with 1 groove on S. and 4 grooves on the E. sides, from which,

A Fir, 30 ins. diam., bears N. 60°E., 63 lks. dist.
Marked T. 22 S., R. 9 W., S. 28 B. T.

A Fir, 36 ins. diam., bears S. 76°W., 38 lks. dist.
Marked C. C. T. 22 S., R. 9 W., S. 28-29 B. T.

A Fir, 50 ins. diam., bears N. 61°W., 12 lks. dist.
Marked T. 22 S., R. 9 W. S 29 B. T.