

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS		
40.00	<p>Set Maple post, $4\frac{1}{2}$ feet long, 4 ins. square, 24 ins. in ground on flat for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ g. on the West face, from which,</p> <p>A Fir, 18 ins. diam., bears S.80*E., 55 lks. dist. Marked $\frac{1}{4}$ S. B. T.</p> <p>A Fir, 24 ins. diam., bears S.73*W., 28 lks. dist. Marked $\frac{1}{4}$ S. B. T.</p>	
45.00	<p>Top of ridge, Course E. and W. Descend.</p>	+ 200
59.75	A creek, 2 lks. wide, Course S.20*W.	
71.25	A creek, 1 lk. wide, Course S.80*W.	
73.98	<p>Intersected E. and W. line, 731 lks. N.89*52'E., of the corner to secs. 30 and 31, which is a post 30 ins. above ground, 4 ins. square, firmly set, and marked T. 22 S., S 29 on the NE., R. 9 W., S. 32 on the SE., S 31 on the SW. and S. 30 on the NW. faces, with 1 notch on the S. and 5 notches on the East edges.</p> <p>I obliterated marks on the NE., and NW. faces and added T. 22 S., on the SW. face, from which,</p> <p>A Fir, 12 ins. diam., bears S.60*E., 38 lks. dist. Marked T. 22 S., R. 9 W., S. 32 B. T.</p> <p>A Fir, 10 ins. diam., bears S.45*W., 8 lks. dist. The B. T. in sec. 29 had been blown down, I marked,</p> <p>A Fir, 10 ins. diam., bears N.78*E., 22 lks. dist. Marked T. 22 S., R. 9 W., S. 31-32 B. T.</p> <p>Set Alder post, 4 ins. square, $4\frac{1}{2}$ feet long, 24 ins. in ground for closing corner to secs. 29 and 30, ^{C. C. on the N. and T. 22 S.} on the E. R. 9 W., S. 30 on the W. faces, with 1 groove on the S. and 5 grooves on the E. sides, from which,</p> <p>A Fir, 10 ins. diam., bears N.29*E., 44 lks. dist. Marked T. 22 S., R. 9 W., S. 29 B. T.</p> <p>A Fir, 60 ins. diam., bears S.8*W., 21 lks. dist.</p>	