

County Surveyor's Record, Douglas County, Oregon

Resurvey of the West Bdy. of T. 22 S., R. 8 W.

CHAINS

on the N. edges, from which,

A Fir, 48 ins. diam., bears N.32\*E., 24 lks. dist.

Marked T. 22 S., R. 8 W., S. 6 B. T.

A Fir (stump), 20 ins. diam., bears S.64\*E., 47 lks. dist.

Marks grown over.

A Fir, 12 ins. diam., bears S.42\*W., 42 lks. dist.

Marks grown over.

A Fir, 36 ins. diam., bears N.45\*W., 6 lks. dist.

Marked T. 22 S., R. 9 W., S. 1 B. T.

Practically agreeing with notes furnished me by the U. S. Surveyor General.

Thence, I run,

North, between secs. 1 and 6.

Va. 20\*E.

Ascend.

6.50 Top of ridge, Course NW. and SE. + 150

Descend.

16.75 A creek, 2 lks. wide, Course SE. - 200

Ascend.

25.50 Top of ridge, Course E. and W. + 250

Descend.

36.50 A creek, 5 lks. wide, Course E. - 100

Ascend.

39.41 The 1/4 sec. corner, as the old post was badly decayed, I set a Fir post, 4 1/2 feet long, 4 ins. square, 24 ins. in ground, on steep hillside sloping South, marked 1/4 sec. on the West face, from which,

A Maple, 14 ins. diam., bears N.70\*E., 20 lks. dist.

Marks grown over.

45.00 A Fir, 10 ins. diam., bears N.55\*W., 46 lks. dist. Top of ridge, E. and W. Marks grown over. + 150

Descend.

53.75 A creek, 2 lks. wide, Course NE. - 75