

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS

Commenced at the corner to secs. 22, 23, 26 and 27,  
which is a granite stone 10 x 8 x 4 ins. above ground,  
marked with 2 notches on the S. and E. sides.

I marked,

A dead Fir, 50 ins. diam., bears N.42\*E., 29 lks. dist.

Marked T. 22 S., R. 9 W., S. 23 B. T.

A dead Fir, 48 ins. diam., bears S.55\*E., 52 lks. dist.

Marked T. 22 S., R. 9 W., S. 26 B. T.

A dead Fir, 24 ins. diam., bears S.51\*W., 118 lks. dist.

Marked T. 22 S., R. 9 W., S. 27 B. T.

A dead Fir, 36 ins. diam., bears N.41\*W., 88 lks. dist.

Marked T. 22 S., R. 9 W., S. 22 B. T.

Thence, I run,

N.89\*29'E., between secs. 23 and 26.

Va. 19\*20'E.

Ascend.

7.25 Top of ridge, Course N. and S.

+ 200

Descend.

17.25 Canyon, Course SE.

27.00 Pass over spur.

30.25 A creek, 1 lk. wide, Course S.

Pass over spur.

39.50 Rock 40 feet high.

42.10 To a point 20 lks. North of the 1/2 sec. corner. Could not  
find stone.

I set sand stone, 12 x 12 x 8 ins., 8 ins. in ground on  
hillside sloping South, marked 1/2 S on North West face,  
from which,

A Fir, 16 ins. diam., bears North, 18 lks. dist.

Marked 1/2 Sec. B. T.

As this tree had been blown down, I marked,

A Maple, 6 ins. diam., bears S.6\*E., 25 lks. dist.