

East Boundary of T. 22 S., R. 10 W.,  
 as surveyed by W. H. Byars, Deputy Surveyor, under contract  
 No. 202, dated March 11, 1874.

CHAINS		
	Beginning at the established meander corner between secs. 13 & 18, Tp. 22 S., Rs. 9 and 10 West, W. M. Corner on North side of river and East side of creek. Corner according to notes furnished me stands south of sec. cor.	
	Var. 18* East	
	South on a true line	
	Base, 470 lks. East, Angle opposite 29 3/4*, dist. over 8.26 chs.	
8.26	Left bank of river.	
8.54	Set meander post from which  An alder, 6 ins. diam., bears S.44*E. dist. 51 lks. An alder, 8 ins. diam., bears S.41*W. dist. 12 lks.	
13.14	Begin steep ascent.	Level
25.04	Set post cor. to secs. 13, 18, 19 & 24.  A fir, 20 ins. diam., bears N.10*E. dist. 76 lks. A fir, 6 ins. diam., bears S.75*E. dist. 33 lks. A fir, 14 ins. diam., bears S.52*W. dist. 5 lks. A fir, 24 ins. diam., bears N.5*W. dist. 12 lks.  Land along river, 1st rate. Remainder, mountainous, 3rd rate.  Timber, fir on mountains. Maples in valleys.	+800
Subdivisions of T. 22 S., R. 10 W. Same Deputy and Contract.		
	West, on true line between secs. 13 & 24.  Var. 18 3/4* East.	
2.50	Top of spur, course N.	+100
23.50	A creek, 3 lks. wide, course N.	-800
33.00	Enter bottom & clearing, course NE. & SW.	-800
40.00	Set maple post for 1/4 sec. cor. from which  A maple stub, 60 ins. diam., 10 ft. high, bears N.3*W. dist. 54 lks.  A fir, 48 ins. diam., bears S.16*E. dist. 308 lks.	