

County Surveyor's Record, Douglas County, Oregon

1737

Subdivisions of T. 22 S., R. 10 W.  
 As surveyed by W. H. Byars, Deputy Surveyor, Under Contract  
 No. 274, dated Sept. 10, 1877.

CHAINS	
	Beginning at the established cor. to secs. 25, 30, 31 & 36. And run West, on a true line bet. secs. 25 & 36. Var. 19*E.
15.00	A creek, 5 lks. wide, course S.
29.50	Camp Creek, 40 lks. wide, course W. Along creek..
36.50	Leave same.
40.00	Set a maple post, 40 ins. diam., for the $\frac{1}{4}$ sec. cor. from which A fir, 60 ins. diam., bears S.15*E. 27 lks. A fir, 24 ins. diam., bears S.20*W. 56 lks.
48.00	Camp Creek, 100 lks. wide, course N.80*W.
62.50	Camp Creek, 100 lks. wide, course NW.
80.00	Marked a fir, 5 ins. diam., for the cor. to secs. 25, 26, 35 & 36, from which An alder, 20 ins. diam., bears N.65*E. 67 lks. A maple, 5 ins. diam., bears S.40*E. 63 lks. A fir, 5 ins. diam., bears S.42*W. 64 lks. A maple, 24 ins. diam., bears N.30*W. 121 lks. Land, broken, rocky, 3rd rate. Timber same as Township line.
	North, on a true line bet. secs. 25 & 26. Var. 19*East.
5.00	Enter burned timber. November 19, 1877.
31.50	Top of ridge, course E. & W.
40.00	Set stone 2x16x30. And made stone mound for $\frac{1}{4}$ sec. cor. No trees near.
76.00	Top of ridge, course E. & W.
80.00	Set stone 3x14x28 for the cor. to secs. 23, 24, 25 & 26, from which A fir, 6 ins. diam., bears N.88*E. 43 lks. No other green timber near in secs. 23, 25 or 26.