

County Surveyor's Record, Douglas County, Oregon

Portion of North Bdy. of T. 22 S., R. 10 W.

| | |
|--|---|
| CHAINS 2.00 | Creek, 2 lks. wide, course S. |
| 10.50 | Top of spur, course S. |
| 22.50 | Enter creek bottom, course SW. |
| 32.00 | Creek, 75 lks. wide, course S.10*W. |
| 38.00 | Leave creek bottom. |
| 40.00 | Marked a fir, 10 ins. diam., for $\frac{1}{4}$ sec. cor. from which A fir, 6 ins. diam., bears S.10*E. dist. 92 lks. A fir, 5 ins. diam., bears N.87*W. dist. 16 lks. Land on hills, rocky, 3rd rate. Creek bottom, 1st rate. Timber all burned. Underbrush, fir maple, laurel, etc. March 30, 1878. This survey is made at the request of Mr. Harvey who has settled on the frac'l. NW. $\frac{1}{4}$ of Sec. 6. |
| North Boundary of T. 23 S., R. 10 W. As surveyed by William H. Byars, Deputy Surveyor, Under contract No. 292, dated August 7, 1878. | |
| | Beginning at the post, the established cor. to Tp. 23 S., Rs. 9 & 10 West, (cor. established by me as standing) I run West, on North boundary of sec. 1. Var. 19*E. |
| 26.00 | SW. cor. of Tp. 22 S., Rs. 9 & 10 West. Stone & mound standing. |
| 40.00 | Set an alder post, 5 ft. long, 5 ins. diam., 20 ins. in ground for the $\frac{1}{4}$ sec. cor. on N. bdy. of Sec. 1, from which An alder, 5 ins. diam., bears N.30*W. dist. 75 lks. An alder, 6 ins. diam., bears S.80*W. dist. 96 lks. |
| 41.00 | A creek, 2 lks. wide, course SW. |
| 56.50 | Mill Creek, 200 lks. wide, course NW. |
| 66.00 | Set a fir post, 4 ft. long, 4 ins. diam., 20 ins. in ground for the $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 36, from which |