

North Boundary of T. 23 S., R. 10 W.

CHAINS

23 S., Rs. 10 & 11 West, from which

An alder, 30 ins. diam., bears S.30*E. 10 lks.

A vine maple, 10 ins. diam., bears S.10*W. 14 lks.

Description of lands, timber and underbrush unchanged.

East Boundary of T. 22 S., R. 10 W.

As surveyed by Aurelius Todd, Deputy Surveyor, Under
Contract No.629, dated April 24, 1894.

I begin at the established $\frac{1}{4}$ sec. cor. on the N. bdy. of
sec. 6, which is a fir, 14 ins. diam., marked $\frac{1}{4}$ S. on N.
side, from which

A fir, 6 ins. diam., bears S.10*E. 92 lks. dist.

marked $\frac{1}{4}$ S B T.

A fir, 5 ins. diam., bears N.87*W. 16 lks. dist.

marked $\frac{1}{4}$ S B T.

And run

East, on a random line bet. Tps. 21 & 22 S., R. 10 W.

I set temp. mile & half mile corners at each 40 & 80 chs.

(setting the first mile cor. at 40 chs.) a distance of
5 $\frac{1}{2}$ miles at which point I set a temp. cor.

June 30 & July 1, 1894

I then go to the location for the meander corner on the
north or right bank of the Umpqua River bet. secs.
13 & 18 on the Tp. line described as a post with bear-
ing trees but find no traces of the cor. but a part of
of the foundation of Scotts old saw mill still remains
in place. Learning from old residents that this is
the identical mill in its original place as noted in
the field notes furnished me by the Surveyor General,
I run from there S.27*E. 105 lks. and reestablish the
meander cor. by setting a post 4 ft. long, 4 ins. sq.,
24 ins. in the ground marked R 9 W S 18 on E., T 22 S.
M C. on S., R 10 W S 13 on W faces, from which