

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 22 S., R 10 W.

CHAINS	<p>on W. faces.</p> <p>I destroy these marks & at</p> <p>80.00 A stone in place 5x4x3 ft. which I marked with cross (x) at exact cor. point with 2 notches on the E. & 4 notches on the W. faces, for cor. to secs. 34 & 35, from which</p> <p>A fir, 28 ins. diam., bears N.80*E. 12 lks. dist. marked T 22 S R 10 W S 35 B T.</p> <p>A fir, 36 ins. diam., bears S.6*W. 15 lks. dist. marked T 22 S R 10 W S 34 & 35 B T.</p> <p>A fir, 30 ins. diam., bears N.82*W. 10 lks. dist. marked T 22 S R 10 W S 34 B T.</p> <p>A large prominent stone, 30 ft. high bears N.20*W. 30 lks. dist. near top of spur.</p> <p>Land, mountainous, 80.00 chs.</p> <p>Soil, 3rd rate, clay & rocky.</p> <p>Timber, fir. Some good saw timber.</p> <p>Dense undergrowth of thimbleberry.</p> <p style="text-align: right;">July 17, 1894.</p>
	<p>Thence I continue</p> <p>West. along S. bdy. sec. 34.</p> <p style="text-align: right;">Var. 20*15'E.</p> <p>Ascend.</p> <p>.60 Spur, course, N.15*E. + 400 ft. above last stream.</p> <p>Descend</p> <p>7.75 At this point which is a rock on SW. slope, 6 ft. high, 20 ft. long.</p> <p>A fir, 40 ins. diam., bears S.65*W. 32 lks. dist. marked $\frac{1}{4}$ S B T.</p> <p>A fir, 40 ins. diam., bears N.25*W. 39 lks. dist. marked $\frac{1}{4}$ S B T.</p> <p>The post being gone, I marked stone with cross (x) at exact cor. point with $\frac{1}{4}$ S. for $\frac{1}{4}$ sec. cor. on N. bdy. sec. 3.</p> <p>25.00 A dry creek, 8 lks. wide, course N.</p>