

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 22 S., R. 10 W.

CHAINS		
47.50	<p>The established cor. to Tps. 23 S., Rs. 10 & 11 W. which is a vine maple , 5 ins. diam., from which</p> <p>An alder, 30 ins. diam., bears S.30*E. 10 lks. dist. marked T 23 S R 10 W S 6 B T.</p> <p>A vine maple, 10 ins. diam., bears S.10*W. 14 lks. dist., marked T 23 S R 11 W S 1 B T.</p>	
47.50	<p>This cor. being out of alignment & not having been closed upon, I destroy the marks & all traces of cor. & at</p> <p>Set a sandstone 24x16x8 ins., 18 ins. in the ground for cor. to Tp. 23 S., Rs. 10 & 11 W. marked With C C & 6 notches on S., E. & W. edges from which</p> <p>An alder, 4 ins. diam., bears N.89*E. 15 lks. dist. marked T 23 S C C R 10 & 11 W B T.</p> <p>A fir, 12 ins. diam., bears S.3*E.40 lks. dist. marked T 23 S R 10 W C C B T.</p> <p>An alder, 6 ins. diam., bears S.36*W. 38 lks. dist. marked T 23 S R 11 W S 1 C C B T.</p>	
	<p>On this line I found no blazes nor marks of any kind. I therefore established it as a new line & marked it with blazes as usual.</p>	
	<p>From this cor. I continue W. and establish the remainder of the S. bdy. of T. 22 S., R. 10 W. to wit.</p>	
	<p>Ascend</p>	
54.00	<p>Canyon, course S.80*E.</p>	
64.50	<p>Spur, course SE.</p>	+150
70.00	<p>Canyon, course S.</p>	
83.50	<p>Ridge, course S.20*W.</p>	+200
91.50	<p>Canyon, course N.</p>	-150
104.00	<p>At this point the cor. to Tp. 22 S., Rs. 10 & 11 W. bears N. I therefore set a sandstone 20x12x8 ins., 15 ins. in the ground for C. C. to T. 22 S., Rs. 10 & 11 W. marked with C C & 6 notches on E. & W. edges, from which</p> <p>A fir, 36 ins. diam., bears N.73*E. 44 lks. dist. marked T 22 S C C R 10 & 11 W S 31 B T.</p> <p>A fir, 30 ins. diam., bears S.24*W. 12 lks. dist.</p>	