

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 10 W.

CHAINS		
	N.O*1'W. a true line bet. secs. 26 & 27.	
		Var. 20*E.
.50	Descend steep to	
6.00	Mill Creek 140 lks., course, N.20*E.	-300
7.50	Opposite bank	
8.50	Ascend.	
14.00	Spur, course, E.	+300
22.10	Mill Creek, course N.	-300
27.10	In Mill Creek, course N.	
30.25	Leave Mill Creek, course, NE.	
	Ascend.	
36.50	Bluff, 30 ft. high.	
40.00	Set a sandstone 18x14x10 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which An alder, 6 ins. diam., bears S.2*W. 150 lks. dist. marked $\frac{1}{4}$ S B T. A fir, 30 ins. diam., bears E. 68 lks. dist. marked $\frac{1}{4}$ S B T.	
41.00	Spur, course, SE.	+400
56.25	Stream, 2 lks., course E.	-150
75.00	Spur, course, N.75*E.	+ 50
80.00	In Mill creek, course W.	- 150
79.50	Set a sandstone 20x16x10 ins., 15 ins. in the ground for witness cor. to secs. 26 & 27, marked W C with 2 notches on S. & E. edges, from which A maple, 30 ins. diam., bears S.62*E. 80 lks. dist. marked T 22 S R 10 W S 26 W C B T. A v. maple, 4 ins. diam., bears S.20*W. 12 lks. dist. marked T 22 S R 10 W S 27 W C B T. A v. maple, 6 ins. diam., bears N.85*W. 10 lks. dist. marked T 22 S R 10 W S 26 & 27 W C B T. A v. maple, 4 ins. diam., bears N.80*E. 10 lks. dist. marked T 22 S R 10 W S 26 & 27 W C B T.	
	Land, mountainous, 79.50 chs.	
	Soil, 3rd rate.	
	Timber, fir, scattering.	