

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 10 W.

CHAINS	
	According to my special instructions, I run East, on a random line bet. secs. 15 & 22. Var. 20*30'E. Along N. slope, rocky.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
83.30	Intersect N. & S. line 30 lks. N. of cor. to secs. 14, 15, 22 & 23. Thence I run N.89*48' W. a true line bet. secs. 15 & 22. Var. 20*30'East. Descend a spur.
21.50	Mill Creek, 250 lks, course N.25*W.
24.50	Opposite bank, Glass house bears S.20*E. about 5 chs.
40.00	Set a sandstone 20x18x12 ins., 16 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face, from which A fir, 30 ins. diam., bears N.82 $\frac{1}{2}$ *W. 130 lks. dist. marked $\frac{1}{4}$ S B T. A fir, 12 ins. diam., bears S.71*W. 175 lks. dist. marked $\frac{1}{4}$ S B T.
55.50	On top of a rocky spur, course NE. At the E. side of an impassable bluff. Set a post, 4 ft. long, 4 ins. sq., marked W. P. for witness point from which A fir, 5 ins. diam., bears S.13*W. 30 lks. dist. marked with notch and a blaze facing post. A fir, 8 ins. diam., bears N.22*W. 10 lks. dist. marked with a notch & a blaze facing post. Set a flag and offset N. to N. side of river & continue N.89*48'W. At
78.50	Offset back S. to line & marked a fir, 36 ins. diam., W. P. for witness point, from which A fir, 36 ins. diam., bears N.42*W. 25 lks. dist. marked with notch and a blaze facing corner.
83.30	The cor. to secs. 15, 16, 21 & 22.

FD 17X16
STONE -
1934 STATE
SEE C.S. A-3