

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 10 W.

CHAINS

with cross (x) at exact cor. point with C. C. & 3 notches on N. & S. for closing cor. to secs. 18 & 19, from which

A fir, 5 ins. diam., bears N.75*E. 25 lks. dist. marked T 22 S R 10 W S 18 B T.

A fir, 4 ins. diam., bears S.58*E. 12 lks. dist. marked T 22 S R 10 W S 19 B T.

A fir, 5 ins. diam., bears N.28*W. 37 lks. dist. marked T 22 S R 10 W C C S 18 & 19 B T.

Land, mountainous, 85.80 chs.

Soil, 4th rate, rocky.

Dense underbrush & timber of young fir.

Aug. 9, 1894.

From the cor. to secs. 17, 18, 19 & 20, I run S.0*4'E. on a random line bet. secs. 19 & 20.

Var. 20*30'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor. & at

73.80 Intersect E. & W. line 18.50 chs. W. of cor. to secs. 29 & 30.

At point of intersection I marked a stone in place on N. slope, 4 ft. high, 6 ft. wide with cross (x) at exact cor. point with C. C. and 2 notches on S. & 4 notches on E. for closing cor. to secs. 19 & 20, from which

A fir, 12 ins. diam., bears N.61*E. 45 lks. dist. marked T 22 S R 10 W S 20 B T.

A fir, 4 ins. diam., bears S.80*W. 16 lks. dist. marked T 22 S R 10 W C C S 19 & 20 B T.

A fir, 18 ins. diam., bears N.35*W. 27 lks. dist. marked T 22 S R 10 W S 19 B T.

Thence I run

N.0*W. on a true line bet. secs. 19 & 20.

Var. 20*30'E.

Descend.