

Meanders of T. 22 S., R. 10 W.  
Same Deputy and Contract.

CHAINS

Find that the meander cors. along the river had been nearly all destroyed, I attempt to locate them by re-tracing the meanders according to the notes furnished me by the Surveyor General but found it impracticable as the courses and distances did not follow the banks of the river. I therefore made a preliminary survey of the meanders and find them too long by about 3 chs. per mile. I therefore divided this distance proportionally and proceeded to reestablish the meanders of the Umpqua River as follows:

From the meander cor. bet. secs. 14 & 23 on the S. or left bank of the river,

I run with the meanders in sec. 14.

Var. 20°30'E.

<u>Course</u>	<u>Chains</u>	
N.22 $\frac{1}{2}$ *W.	12.00	Along mountain side , slopes to river.
N.16*W.	3.00	Leave steep slope & at
North	5.00	Narrow bottom along river.
N.29*W.	17.00	
N.50*W.	8.00	
N.83*W.	13.00	
West	4.50	
S.75*W.	13.00	
S.69*W.	7.00	Set a post, 4 ft. long, 4 ins. sq., marked T 22 S R 10 W M C on N., S 14 on E., S 15 on W. faces, for meander cor. bet. secs. 14 & 15 from which A maple, 20 ins. diam., bears S.2*W. 48 lks. dist. marked T 22 S R 10 W S 15 M C B T. A maple, 20 ins. diam., bears S.74*E. 66 lks. dist.