

## County Surveyor's Record, Douglas County, Oregon

## Donation Land Claim of E. R. Fiske &amp; W. Sloan.

CHAINS

Land, rocky, broken, mountainous, 3rd rate.

Timber, fir, laurel, maple and dogwood.

Underbrush, same with hazel, etc.

July 26, 1876.

Extracts from Homestead Entry Survey No. 130, made by Frank D. Maxwell, Surveyor Forest Service, under special instructions, dated March 12, 1914; Sec. 31 T. 21 S. R. 10 W.

Retracements and Resurveys.

July 20, 1914: Preliminary to the survey of this Homestead Entry, I make the following retracements:

Commencing at the  $\frac{1}{4}$  sec. cor. on the N. bdy. of sec. 6, T. 22 S., R. 10 W., which is a fir tree, 26 ins. diam., marked and witnessed as described by the Surveyor General.

(Note:- In cutting into this corner tree and bearing trees in order to read the markings I spoil the readings somewhat, so re-mark the corner as follows:)

A fir, 26 ins. diam., (orig.) marked

$\frac{1}{4}$  S. 6 on S. face, from which

A fir, 24 ins. diam., bears S.10\*00'E. 93 lks. dist. (orig.). (This tree partially destroyed, marking left on tree.)

A fir, 8 ins. diam., bears S.26\*10'E. 55 lks. dist. (new) marked  $\frac{1}{4}$  S 6 B T.

Thence I run

S.82\*47'W. (recorded bearing), retracing the N. bdy. of sec. 6.

30.97 I make diligent search for closing cor. of T. 21 S., Rs. 10 and 11 W., but fail to find any trace of it.

38.31 Fall 386 lks. S.7\*13'E. of point for cor. of T. 22 S., Rs. 10 and 11 W. After diligent search I am unable to find any trace of the stone reported set for this cor. The point for this cor. falls on a very steep NE. slope, covered with fern, brake and undergrowth. The