

## East Boundary of T. 22 S., R. 11 W.

## CHAINS

- 14.20 Top of a spur, course W.
- 18.40 Top of a spur, course W.
- 40.00 A point about 300 ft. above sec. cor.  
Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on W. face, from which
- A maple, 10 ins. diam., bears N.75\*W. 123 lks. dist. marked  $\frac{1}{4}$  S B T.
- A maple, 20 ins. diam., bears N.34\*E. 58 lks. dist. marked  $\frac{1}{4}$  S B T.
- Continue to ascend.
- 43.60 Top of high ridge, course E. & W. about 200 ft. above  $\frac{1}{4}$  sec. cor.  
Thence over W. slope.
- 55.40 Top of a ridge, course S.20\*W. and descend abruptly to
- 64.60 Dry creek bed, 2 lks. wide, course SW. about 300 ft. below top of last ridge, and ascend.
- 71.20 Top of a ridge, course SW. & descend.
- 78.65 Stream, 4 lks. wide, course SW. and ascend.
- 85.66 At this point I establish the cor. to secs. 7, 12, 13 & 18 in accordance with instructions received from the Surveyor General to run the East boundary of sec. 12 equal in length to the W. bdy. of the same, which I had already ascertained to be 85.66 chs. I therefore set a post 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to secs. 7, 12, 13 & 18 marked T 22 S S 7 on NE., R 10 W S 18 on SE., R 11 W S 13 on SW. and S 12 on NW. faces, with 2 notches on N. and 4 notches on S. edges, from which
- A fir, 20 ins. diam., bears N.37\*E. 39 lks. dist. marked T 22 S R 10 W S 7 B T.
- A fir, 20 ins. diam., bears S.31\*E. 30 lks. dist. marked T 22 S R 10 W S 18 B T.