

## County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 22 S., R. 11 W.

## CHAINS

- 29.00 Stream, 1 lk. wide, course E. about 300 ft. Below top of last spur.  
Ascend abruptly.
- 35.50 Top of a spur on E. slope about 300 ft. above stream  
Descend.
- 40.00 Set a stone 16x12x8 ins., 10 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on W. face, from which  
A fir, 10 ins. diam., bears N.3\*E. 12 lks. dist. marked  $\frac{1}{4}$  S B T.  
An alder, 5 ins. diam., bears S.86\*W. 4 lks. dist. marked  $\frac{1}{4}$  S B T.
- 43.60 Stream, 1 lk. wide, course E. about 300 ft. below top of last spur.  
Ascend.
- 48.95 A fir, 18 ins. diam. marked with 2 notches on N. & S. sides.
- 56.60 Summit of mountain, trail on top course NW. & SE.
- 68.50 Begin to descend.
- 78.00 Gulch course E. about 300 ft. below top of mountain.  
Ascend.
- 80.00 This point falling on bed rock sloping to the N. I marked a cross(x) at exact cor. point for cor. to secs. 19, 24, 25 & 30, with 4 notches on N. and 2 notches on S. edges, from which  
A fir, 12 ins. diam., bears N.43\*E. 13 lks. dist. marked T 22 S R 10 W S 19 B T.  
A fir, 6 ins. diam., bears S.37\*E. 21 lks. dist. marked T 22 S R 10 W S 30 B T.  
A fir, 10 ins. diam., bears S.33\*W. 13 lks. dist. marked T 22 S R 11 W S 25 B T.  
A fir, 6 ins. diam., bears N.11\*W. 33 lks. dist. marked T 22 S R 11 W S 24 B T.
- Land, 80 chs. mountainous.