

Retracement of Portion of E. Bdy. of T. 22 S., R. 12 W.

CHAINS	
39.78	<p>South, on a random line, on E. bdy. of sec. 24.</p> <p>I close 93½ lks. E. of the old ¼ sec. cor. which is nearly destroyed, cor. missing but bearing trees in position.</p>
79.36	<p>I close 187 lks. E. of the old cor. of secs. 24 and 25, already described.</p> <p>The true bearing of this mile is therefore N. 1°21'E.</p> <p style="text-align: right;">May 2, 1910.</p>
8.50	<p>At the cor. of secs. 24 and 25 on the E. bdy. of the Tp.</p> <p>Thence I run</p> <p>N.1°21'E., on a true line on E. bdy. of sec. 24.</p> <p>Descend general N. slope thru heavy timber and dense undergrowth.</p>
25.50	<p>Spring branch, 2 lks. wide, course E.</p>
25.50	<p>Spur, 150 ft. high, slopes NE.</p>
28.90	<p>Spring branch, 2 lks. wide, course E.</p>
36.51	<p>Spur, 300 ft. high, bears NE. & SW.</p> <p>Descend N. slope to creek.</p>
39.43	<p>Creek, 3 lks. wide, course NE. 200 ft. below spur.</p>
39.58	<p>The old ¼ sec. cor. I destroy all trace of this old ¼ sec. cor. and reestablish it at the same point as follows:</p>
	<p>Set a sandstone, 12x10x8 ins., 8 ins. in the ground for ¼ sec. cor. marked ¼ on W. face; from which</p>
	<p style="padding-left: 40px;">Spruce, 12 ins. diam., bears S.80°W. 40 lks. dist. marked ¼ S 24 B T.</p>
	<p style="padding-left: 40px;">Hemlock, 24 ins. diam., bears N.73°30'W. 49 lks. dist., marked ¼ S 24 B T.</p>
52.27	<p>Intersect the old decayed stump of closing cor. of secs. 18 and 19 with old bearing trees. The stump has fallen to the ground and the marks are no longer visible on witness trees.</p> <p>I destroy all trace of this old cor. and reestablish at the same point as follows:</p>