

County Surveyor's Record, Douglas County, Oregon

1983

Coast Meridian T. 22 S. R. 12 and 13 W.
As surveyed by Harvey Gordon, Deputy Surveyor, under
Contract No. 68, dated February 2, 1857.

CHAINS		
	South, between Secs. 1 and 6.	
	Va. 19*20'E.	
28.50	Right Bank of Umpqua River Measured Base S.43*W. 27.00 chains. Object in line on left Bank bears S.13*45'E. Hence by traverse 94.99 over to meander corner at foot of Bluff.	
40.00	1/4 Sec. cor. in River.	
80.00	Cor. of Secs. 1, 6, 7 and 12 in River. Land, sandy. Soil, 3rd rate. No timber.	
<hr/>		
	South, bet. Secs. 7 and 12.	
	From triangulations on last mile I find	
43.49	to meander cor. at foot of Bluff.	
43.99	Set witness to meander corner.	+ 100
	Planted post, from which	
	A Spruce, 100 ins. diam., bears S.26*W., 25 lks. dist.	
	A Spruce, 10 ins. diam., bears S.67*E., 27 lks. dist.	
49.50	Top of hill.	- 250
50.75	Trail, course W.	
52.65	Spruce, 40 ins. diam.	
53.75	Trail from the Rock to Providence.	
78.00	Stream 3 lks. wide, course NE.	
80.00	Set post, cor. Secs. 7, 12, 13 and 18, from which	
	A Spruce, 40 ins. diam., bears N,54*E., 42 lks. dist.	
	A Spruce, 50 ins. diam., bears S,52*E., 15 lks. dist.	
	A Spruce, 50 ins. diam., bears N.81 1/2*W., 32 lks. dist.	
	A Spruce, 15 ins. diam., bears S,37*W., 53 lks. dist.	