

SUB-DIVISIONS OF T. 22 S., R. 12 W. W.M.

CHAINS		
	East on Random line between Sections 14 and 23.	
	Va. 18*E.	
40.00	Set temp. $\frac{1}{4}$ Sec. Corner. July 8th, 1874.	
80.00	Found no corner or signs. Set temp. corner until run line between Sections 13 and 24.	
80.91	Intersect line 45 lks. North of Corner North 89*41' West on true line.	
38.00	Top of Spur, course N.	+200
40.45	Set post for $\frac{1}{4}$ Sec. corner from which A Cedar, 20 ins. diam., bears S.30*W., 11 lks. dist. A Cedar, 30 ins. diam., bears N.65*E., 20 lks. dist.	
53.00	Foot of hill. Course N and S.	-100
54.00	A creek 25 lks. wide, course N, enter clearing.	-100
57.50	Leave clearing. Foundation of house 1 chain N. of line.	
67.00	Top of Spur.	+200
78.00	A creek 1 lk. wide course E.	
80.91	To Section corner. Land, high, rolling. Soil, 3rd rate. Timber, principally Fir, Cedar and Spruce.	
	July 10th, 1874.	
	Begin at the established corner to Sections 13, 14, 11 and 12 and run South on true line.	
	Va. 18*East.	
1.00	Begin descent.	
13.00	A creek 3 lks. wide, course SW.	-200
14.50	Begin ascent	-200
35.70	A creek 1 lk. wide course W.	-150
40.00	Set Fir post for $\frac{1}{4}$ Sec. corner from which A Hemlock, 12 ins. diam., bears N.65*E., 13 lks. dist. A Fir, 40 ins. diam., bears N.60*W., 35 lks. dist.	
40.70	A creek 2 lks. wide, course W.	
47.00	Top of ridge, course SW.	+200
61.00	Enter Valley, course E and W. Enter small field.	-200