

County Surveyor's Record, Douglas County, Oregon

NORTH BOUNDARY OF T. 23 S., R. 12 W. W.M.

CHAINS

West, on North boundary Sec. 2.

Va. $19\frac{1}{2}$ *E.

Looking ahead it will be impossible to run line, so I offset South 10 chs. West 2500 chs. South 5 chs. West 4000, chs. North 5 chs. West 1500 chs. to line, then North 10.00 chs. to corner for Secs. 2, 3, 34 and 35. Set Crabapple post, 6x6 by 5 ft. long in ground, from which

An Alder, 24 ins. diam., bears S.61*W., 42 lks. dist.

A Willow, 4 ins. diam., bears N.46*W., 60 lks. dist.

An Alder, 12 ins. diam., bears N.32*E., 202 lks. dist.

Nothing near in Sec. 2 suitable to mark.

This post stands in a barley patch of a settler by the name of Carlson.

Soil on mountain, hardly none at all; on bottom near post, 1st rate. No timber on mountain.

Feb. 6th, 1880.

West, on North boundary Sec. 3.

Va. $19\frac{1}{2}$ *E.

- 7.00 Ascend mountain covered with timber.
 - 33.00 Top of mountain, descend slope NW.
 - 40.00 Set Alder post, 5x5 by 5 ft. long in ground for $\frac{1}{4}$ Sec. corner, from which
 - An Alder, 12 ins. diam., bears N.9*W., 17 lks. dist.
 - An Alder, 12 ins. diam., bears S.72*W., 29 lks. dist.
 - 45.50 Intersect lake. Marked an Alder, 10 ins. diam., for witness corner. No witness trees.
- Cross over on drift, distance across 6.00