

SUBDIVISIONS OF T. 22 S., R. 12 W., W.M.

CHAINS		
35.20	A trail on top of spur, bears S.20*W and N.20*E.	+300
40.00	<p>On East slope of spur, set a Hemlock post, 3 ft. long, 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ Sec. corner marked $\frac{1}{4}$ S on West face, from which</p> <p>A Fir, 36 ins. diam., bears N.50*E., 10 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A Fir, 36 ins. diam., bears N.5*W., 11 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>Begin descent.</p>	+50
42.00	Foot of descent, begin ascent.	-60
46.50	<p>Top of divide, between waters flowing into Schofield River and into the lakes, bears E and W.</p> <p>Begin descent of SW slope.</p>	+100
62.50	A canyon, course SW; begin ascent of W slope.	-300
67.50	Top of spur, E and W; begin descent.	+120
71.20	A canyon, course NW; begin very steep ascent of the backbone of a spur, bears N and S.	-60
77.00	Change ascent to W slope of spur.	
80.00	<p>Set a Maple post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to Secs. 25, 26, 35 and 36, marked T 22 S S 25 on NE R 12 W S 36 on SE S 35 on SW S 26 on NW faces, with 1 notch on S and E edges, from which</p> <p>An Alder, 16 ins. diam., bears N.35*E., 45 lks. dist., marked T 22 S R 12 W S 25 B T.</p> <p>An Alder, 3 ins. diam., bears S.55*E., 233 lks. dist., marked T 22 S R 12 W S 36 B T.</p> <p>A Fir, 36 ins. diam., bears S.58*W., 17 lks. dist., marked T 22 S R 12 W S 35 B T.</p> <p>A Fir, 40 ins. diam., bears N.88*W., 23 lks. dist., marked T 22 S R 12 W S 26 B T.</p>	+600
	<p>Land, mountainous.</p> <p>Soil, rocky with loam 6 ins. on top, 3rd rate.</p>	