

SUBDIVISIONS OF T. 22 S. R. 12 W. W.M.

CHAINS		
24.75	A canyon, course E., begin ascent.	-100
27.75	Top of spur, bears E and W.	+180
31.00	Begin descent on E. slope.	
38.00	Leave E. slope, very steep descent.	-60
40.00	Set a Fir post, 3 ft. long, 3 ins. sq. 24 ins. in the ground, for $\frac{1}{2}$ Sec. cor. marked $\frac{1}{2}$ S on W. face, from which <div style="margin-left: 40px;">A Fir, 27 ins. diam., bears N.51*W., 15 lks. dist., marked <math>\frac{1}{2}</math> S B T.</div> <div style="margin-left: 40px;">A Hemlock, 36 ins. diam., bears S.85*E., 17 lks. dist., marked <math>\frac{1}{2}</math> S B T.</div>	-50
42.00	Descend along E. slope.	
49.00	A canyon, course E, begin ascent of E. slope.	-100
56.00	Top of spur, bears E and W, begin descent.	+160
59.00	A canyon, course NE, begin ascent.	-120
61.00	Top of spur, bears E and W, begin descent.	+100
67.00	Enter flat bottom, bears N and S.	-150
68.60	A branch 5 lks. wide, course S.30*W.	
71.00	A branch 3 lks. wide, course W.	
72.00	Begin to ascend.	
76.50	Top of ascent, begin descent.	+ 80
78.50	A canyon, course W., begin ascent.	- 50
80.00	Set a Hemlock post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, for cor. to secs. 20, 21, 28 and 29, marked T 22 S S 21 on NE., R 12 W S 28 on SE., S 29 on SW., S 20 on NW. faces, with 2 notches on S and 4 notches on E edges, from which <div style="margin-left: 40px;">A Spruce, 48 ins, diam., bears N.70*E., 5 lks. dist., marked T 22 S R 12 W S 21 B T.</div> <div style="margin-left: 40px;">A Hemlock, 6 ins. diam., bears S.35<math>\frac{1}{2}</math>*E., 44 lks. dist., marked T 22 S R 12 W S 28 B T.</div> <div style="margin-left: 40px;">A Fir, 40 ins. diam., bears S18<math>\frac{1}{2}</math>*W., 31 lks. dist., marked T 22 S R 12 W S 29 B T.</div> <div style="margin-left: 40px;">A Hemlock, 15 ins. diam., bears N.43<math>\frac{1}{2}</math>*W., 25 lks. dist., marked T 22 S R 12 W S 20 B.T.</div>	