

Subdivisions of T. 22 S., R. 13 W.

CHAINS	North, bet. secs. 25 and 26.
5.00	Offset W. 15.00 chs. to avoid Butte.
40.00	Return to line. Set qr. sec. post, made a witness cor. N.68*W., 49 lks. dist. in a natural mound 5 ft. high; drove charred stake.
80.00	Set post cor. of secs. 23, 24, 25 and 26, from which A pine, 6 ins. diam., bears N.0¼*E., 1179 lks. dist. A pine, 6 ins. diam., bears N.5¼*W., 1139 lks. dist. No other bearing trees near. Land, sandy. Soil, 3rd rate.
<hr/>	
	East, on random bet. secs. 24 and 25. Var. 19*30'E.
40.00	Set temp. qr. sec. post.
53.75	W. side of Clear Lake. Base, S. 5.00 chs. Angle opposite, 15*. Distance over, 18.65 chs.
72.40	To snag in water.
79.48	To arm of Clear Lake; thence S.0*15'. S.35*E., 2.00 chs. to meander post in E. bdy. of sec. 25.
80.63	Intersect N. 15 lks. from sec. cor. in lake. N.89*54'W., on true line bet. secs. 24 and 25.
1.15	Set meander post on arm of lake. A spruce, 50 ins. diam., bears S.11*W., 40 lks. dist. An alder, 20 ins. diam., bears N.70*W., 53 lks. dist.
4.00	Ridge, course N & S.
7.33	Set meander post on E. bank of lake. A R. fir, 24 ins. diam., bears S.10*W., 10 lks. dist. A spruce 24 ins. diam., bears N.50*W. 38 lks. dist.