

-1-

County Surveyor's Record, Douglas County, Oregon

2212

East Bdy. of T. 23 S., R. 2 W.,
As surveyed by John A. McQuinn, Deputy Surveyor
Under Contract No. 466
Dated April 5, 1883

CHAINS	
	I begin at the corner to Townships 23 & 24 S. Rs. 1 & 2 W
	I run
	North between Secs. 31 & 36
	Va. $19\frac{1}{2}$ * East
	Through heavy timber
10.31	A brook 4 lks. wide course E
11.16	A hemlock 20 ins. diam.
12.50	A brook 3 lks. wide course SE
28.90	A fir, 40 ins. diam.
40.00	Set a fir post 3 ft. long 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. corner marked $\frac{1}{4}$ S on W face, from which A fir, 18 ins. diam., bears S.87*W., 23 lks. dist. Marked $\frac{1}{4}$ S B T A cedar, 24 ins. diam., bears East 58 lks. dist. Marked $\frac{1}{4}$ S B T
42.50	A brook 5 lks. wide course N.50*E
48.30	A fir, 20 ins. diam.
80.00	Set a cedar post 4 ft. long 24 ins. in the ground 4 ins. sq. for corner to Secs. 25, 30, 31 & 36 marked T 23 S S 30 on NE., R 1 W S 31 on SE., R 2 W S 36 on SW., and S 25 on NW faces with 5 notches on N and 1 notch on S edges, from which A fir, 20 ins. diam., bears S.45*E., 52 lks. dist. Marked T 23 S R 1 W S 31 B T A fir, 6 ins. diam., bears N.32*E., 26 lks. dist. Marked T 23 S R 1 W S 30 B T A fir, 20 ins. diam., bears S.38*W., 7 lks. dist. Marked T 23 S R 2 W S 36 B T A fir, 24 ins. diam., bears N.57*W., 31 lks. dist. Marked T 23 S R 2 W S 25 B T
	Land, mountainous
	Soil, 3rd rate
	Densely covered with forest of pine, fir, hemlock, maple, laurel & dogwood.