

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 23 S., R. 1 W.

CHAINS		
	Dense undergrowth of rhododendron, vine-maple, and chin- quapin, 80.76 chs. Soil, sandy and rocky, 3rd and 4th rates	
	N.2°W. bet. secs. 26 & 27 Va. 19°E.	
28.00	Descending through timber Creek, 2 lks. wide, course NE	-300
	Ascend	
29.50	Top of spur, course E	+25
	Descend	
33.40	Creek, 1 lk. wide, course E	-50
	Ascend	
36.00	Top of spur, course E	+75
	Descend	
39.50	Ravine, course E	-100
	Ascend	
40.00	Set a post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face, from which A fir, 4 ins. diam., bears S.87°E., 8 lks. dist. Marked $\frac{1}{4}$ S B T A hemlock, 8 ins. diam., bears S.57°W., 18 lks. dist. Marked $\frac{1}{4}$ S B T	
60.00	Top of spur, course E.	+100
	Descend	
80.00	Set basalt stone, 18x10x6 ins., 14 ins. in the ground marked with 2 notches on S and E edges for cor. to secs. 22, 23, 26, 27, from which A fir, 30 ins. diam., bears N.15°E., 40 lks. dist. Marked T 23 S R 1 W S 23 B T A fir, 24 ins. diam., bears S.24°W., 125 lks. dist. Marked T 23 S R 1 W S 27 B T A fir, 24 ins. diam., bears S.54°E., 29 lks. dist. Marked T 23 S R 1 W S 26 B T	-400