

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 1 W.

CHAINS		
39.90	Set a post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, marked $\frac{1}{4}$ S on W face for $\frac{1}{4}$ sec. cor., from which A fir, 36 ins. diam., bears N.50*W., 23 lks. dist. Marked $\frac{1}{4}$ S B T A hemlock, 30 ins. diam., bears S.85*W., 36 lks. dist. Marked $\frac{1}{4}$ S B T	
62.75	Top of ridge, bears N & S Descend	+350
79.80	To the cor. to secs. 21, 22, 27 and 28 Land, mountainous, 79.80 chs. Timbered with fir and hemlock Undergrowth mountain-balm and vine-maple Soil, sandy and rocky 3rd and 4th rate	
<hr/>		
	Beginning at the cor. to secs. 32 and 33 on S boundary of Tp. thence I run N.0*3*W bet. secs. 32 and 33 Va. 20*E Ascending through timber	
20.75	Top of spur, course NE Descend	+300
40.00	Set basalt stone, 18x9x5 ins. 14 ins. in the ground, marked $\frac{1}{4}$ on W face for $\frac{1}{4}$ sec. cor. from which A hemlock, 12 ins. diam., bears S.23*E., 29 lks. dist. Marked $\frac{1}{4}$ S B T A fir, 12 ins. diam., bears S.3*W., 31 lks. dist. Marked $\frac{1}{4}$ S B T	
50.00	Creek, 1 lk. wide, course NW	
58.25	Same creek, course NE	-300
80.00	Top of spur NE	+100