

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 23 S., R. 1 W.

CHAINS		
	<p>Set a post, 4 ft. long, 4 ins. sq. 24 ins. in the ground for cor. to secs. 28, 29, 32 and 33 marked T 23 S S 28 on NE., R 1 W S 33 on SE., S 32 on SW, and S 29 on NW faces with 1 notch on S and 4 notches on E edges, from which</p> <p>A hemlock, 4 ins. diam., bears N.73<math>\frac{1}{2}</math>*E., 13 lks. dist. Marked T 23 S R 1 W S 28 B T</p> <p>A hemlock, 4 ins. diam., bears S.22*E., 18 lks. dist. Marked T 23 S R 1 W S 33 B T</p> <p>A hemlock, 4 ins. diam., bears S.66*W., 17 lks. dist. Marked T 23 S R 1 W S 32 B T</p> <p>A hemlock, 4 ins. diam., bears N.37<math>\frac{1}{2}</math>*W., 14 lks. dist. Marked T 23 S R 1 W S 29 B T</p> <p>Land, mountainous, 80.00 chs.</p> <p>Timbered with fir and hemlock, 80.00 chs.</p> <p>Soil, sandy and rocky, 3rd and 4th rate</p>	
<p>40.00</p> <p>80.10</p> <p>23.25</p>	<p>N.89*42'E. on random line between secs. 28 and 33 Va. 20*E.</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>Intersect N and S line 19 lks. N of cor. to secs. 27, 28, 33 and 34. Thence I run S.89*50'W. on true line between secs. 28 and 33 Va. 20*E.</p> <p>Ascending through timber</p> <p>Top of spur, course NW</p> <p>Descend</p>	<p>+100</p>