

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 23 S.

CHAINS

From which

A fir, 16 ins. diam., bears N.60°E., 27 lks. dist.

Marked T 23 S R 1 E S 31 B T. (Old BT.)

A fir, 38 ins. diam., bears S.40°E., 60 lks. dist.

Marked T 24 S R 1 E S 6 B T. (Old BT.)

A fir, 40 ins. diam., bears S.34 $\frac{1}{2}$ °W., 47 lks. dist.

Marked T 24 S R 1 W S 1 B T. (Old BT.)

A fir, 8 ins. diam., bears N.8°W., 63 lks. dist.

Marked T 23 S R 1 W S 36 B T. (New BT.)

Thence

N.0°05'W., on a true line, resurveying W. bdy. of sec. 31

Over mountainous land, through heavy timber and dense
undergrowth

Desc. 400 ft. over NW. slope.

22.65 Ravine, water in holes, course NE. Leave heavy timber,
enter widely scattered timber, bears NE and SW

Asc. 500 ft. to ridge, over SE slope.

38.97 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass
cap marked

$\frac{1}{4}$ S36 |

1925