


County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of the Willamette Meridian, through T. 23 S.

CHAINS

the ground, for cor. of secs. 30 and 31 only, with brass cap marked



from which

A fir, 24 ins. diam., bears N.23*E., 72 lks. dist.

Marked T 23 S R 1 E S 30 B T.

A fir, 20 ins. diam., bears S.32*E., 38 lks. dist.

Marked T 23 S R 1 E S 31 B T.

Land, mountainous

Soil, coarse loam, rocky; 2nd and 3rd rate.

Timber, fir, hemlock, pine, and chinquapin.

Undergrowth, vine-maple, rhododendron, chinquapin, huckleberry, snowbrush, and second growth fir and hemlock.

N.0*57'E., on W. bdy. sec. 30.

Desc. 32 ft. over NW. slope, through heavy timber and dense undergrowth.

1.55 Dry ravine, course NW.; asc. 230 ft. over SW. slope.

8.65 Spur, slopes W.; desc. 37 ft. over NW. slope.

12.30 Dry ravine, course NW.; asc. 15 ft. over SW. slope.

15.30 Spur, slopes W.; Desc. 265 ft. over steep N. slope.

21.65 Dry ravine, course W.; asc. 160 ft. over SW. slope.

27.15 The old 1/4 sec. cor., which is a basalt stone, 6x10x8 ins.

above ground, firmly set, marked 1/4 on W. face; from which

A fir snag, 30 ins. diam., bears S.40*E., 38 lks. dist., marked 1/4 S B T.

A fir snag, 50 ins. diam., bears West, 38 lks. dist., marked 1/4 S B T.