

Retracement and Dependent Resurvey  
of the Willamette Meridian, through T. 23 S.

CHAINS	
	<p>I now change this cor. to refer to sec. 25 only, and mark the stone <math>\frac{1}{4}</math> S 25 on W. face; from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S.77<math>\frac{1}{2}</math>*W., 69 lks. dist. Marked <math>\frac{1}{4}</math> S 25 B T. (new BT.)</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N.29*W., 47 lks. dist. Marked <math>\frac{1}{4}</math> S 25 B T. (new BT.)</p> <p>Thence</p> <p>N.1*30'E., continuing measurement.</p> <p>Asc. 30 ft. to</p>
28.55	Spur, slopes W.; desc. 186 ft. over steep N. slope.
32.35	Dry ravine, course NW.
34.55	Dry ravine, course W.; asc. 123 ft. over SW. slope.
40.01	(40.00 chs. northing from the sec. cor.) Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 30 only, with brass cap marked
	$\frac{1}{4}$ S30 1925
	from which
	<p>A fir, 38 ins. diam., bears N.40*E., 47 lks. dist. Marked <math>\frac{1}{4}</math> S 30 B T.</p> <p>A fir, 28 ins. diam., bears S.42*E., 53 lks. dist. Marked <math>\frac{1}{4}</math> S 30 B T.</p>
40.45	Desc. 12 ft. over NW. slope.
41.30	Dry draw, course W.; asc. 233 ft. over SW. slope.
53.35	Spur, slopes W.; desc. 350 ft. over steep NW. slope.
65.56	<p>The point for the old cor. of secs. 19, 24, 25, and 30, determined by reference to the original bearing trees.</p> <p>I now change this cor. to refer to secs. 24 and 25 only, and re-establish the cor. at the exact point as follows</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bed rock, surrounded by a mound of stone, 3 ft. base, 2 ft. high, for cor. of secs. 24 and 25 only, with brass cap marked</p>