

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of the Willamette Meridian, through T. 23 S.

CHAINS

T23S	T23S
S24	R1E
S25	S 30
R1W	1925

from which

A cedar, 15 ins. diam., bears S.36*E., 22 lks. dist.

Marked T 23 S R 1 E S 30 B T., old BT.

on which I now destroy the marks.

A cedar, 15 ins. diam., bears S.8*W., 12 lks. dist.

Marked T 23 S R 1 W S 25 B T. (old BT.)

A fir, 6 ins. diam., bears N.43*W., 22 lks. dist.

Marked T 23 S R 1 W S 24 B T. (new BT.)

The old bearing tree in sec. 19 is gone.

Thence

N.0*47'E., continuing measurement.

Desc. 296 ft. to

80.02 (80.00 chs. northing from the cor. of Secs. 30 and 31.)

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19 and 30 only, with brass cap marked

T23S	T23S
R1W	S19
S24	S30
R1E	R1E
	1925

from which

A fir, 20 ins. diam., bears N.60*E., 22 lks. dist.

Marked T 23 S R 1 E S 19 B T.

A fir, 8 ins. diam., bears S.25*E., 80 lks. dist.

Marked T 23 S R 1 E S 30 B T.

Land, mountainous

Soil, coarse sandy loam, rocky; 2nd and 3rd rate.

Timber, fir, hemlock, madrona and pine.

Undergrowth, vine-maple, rhododendron, huckleberry, and snow brush.