

County Surveyor's Record, Douglas County, Oregon

-10-

Southern Boundary of T. 23 S., R. 2 W., W.M.

CHAINS

And that it was from this closing cor. that the south boundary of Tp. 23 S., R 2 W. was run. Therefore I return to the cor. to T^S 23 and 24 S., Rs. 1 and 2 W. which is a post 4½ft. long and 4 ins. square, firmly set in the ground, marked T. 23 S^S 31 on NE. R 1 W S 6 on SE., T 24 S S 1 on SW., and R 2 W S 36 on NW. faces with 6 notches on each edge, from which,

A Hemlock, 6 ins. diam., bears N.41*E., 9 lks. dist. marked T 23^S R 1^W S 31 B T.

A Red Fir, 36 ins. diam., bears S.58*E., 32 lks. dist., marked T 24 S R 1 W S 6 B T.

A Hemlock, 30 ins. diam., bears S.38*W., 30 lks. dist., marked T 24 S R 2 W S 1 B T.

A White Fir, 30 ins. diam., bears N.68*W., 33 lks. dist., marked T 23 S R 2 W S 36 B.T.

As Tp. 24 S R 2 W. has not been subdivided and consequently no subdivision lines have been closed on either side of this south boundary, I re-survey the same as follows:

Commencing at the cor. to Tp. 23 and 24 S., Rs. 1 and 2 W., I run

West bet. sec. 1 and 36

Va. 20*E.

Through heavy timber, ascend about 200 ft. to

20.90 Trail from Oakland to Bohemia mines on top of ridge, course NW. and SE. and descend.

39.50 The old ¼ sec. cor., a post bears south 23 lks. dist. I destroyed this post and also the marks on the old bearing trees.

40.00 Set a stone 20 x 12 x 7 ins., 15 ins. in the ground for ¼ sec. cor., marked with ¼ on N. face, from which,

A Hemlock, 12 ins. diam., bears N.64*W., 10 lks. dist, marked ¼ S. B T.

A Hemlock, 10 ins. diam., bears S.6*W., 25 lks. dist. marked ¼ S B T.