

County Surveyor's Record, Douglas County, Oregon

-14-

Southern Boundary of T. 23 S., R. 2 W., W.M.

CHAINS

- 2.50 Old sec. cor., a post bears S.40 lks. dist., I destroyed this post, also the marks on the old bearing trees.
- 27.50 Top of ridge, course S. and descend about 400 ft.
- 40.00 Set a Basalt stone 12 x 10 x 6, 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, from which
 A Fir, 40 ins. diam., bears N.50*E., 32 lks. dist., marked $\frac{1}{4}$ S B T.
 A Fir, 40 ins. diam., bears S.15*E., 27 lks. dist., marked $\frac{1}{4}$ S B T.
- 41.00 Old $\frac{1}{4}$ sec. cor., a post bears south, 80 lks. dist., I destroyed this post, also the marks on old bearing trees.
- 65.00 Dry creek bed, 5 lks. wide, course SW. and ascend about 30 ft. to
- 67.50 Top of spur, course SW. and descend about 40 ft. to
- 70.00 Creek, 1 lk. wide, course SW. and ascend about 75 ft.
- 79.75 Old sec. cor., a post bears south 3.75 chs., I destroyed this post, also the marks on the old bearing trees.
- 80.00 Set a Basalt stone 15 x 12 x 5 ins. in the ground for cor. to secs. 4, 5, 32 and 33, marked with 4 notches on E. and 2 notches on W. edges, from which,
 A Fir, 60 ins. diam., bears N.16*30'E., 37 lks. dist., marked T 23 S R 2 W S 33 B T.
 A Fir, 36 ins. diam., bears S.31*30'E., 89 lks. dist., marked T 24 S R 2 W S 4 B T.
 A Fir, 36 ins. diam., bears S.52*W., 35 lks. dist., marked T 24 S R 2 W S 5 B T.
 A Fir, 48 ins. diam., bears N.19*W., 40 lks. dist., marked T 23 S R 2 W S 32 B T.
- Land, mountainous and heavily timbered with Fir and Hemlock.
- Dense undergrowth of Vine-maple.
- Soil, sandy and rocky, 3rd and 4th rate.

80.00 chains.

August 6, 1894