

County Surveyor's Record, Douglas County, Oregon

Western Boundary of T. 23 S., R. 2 W., W.M.

CHAINS

within limits. Therefore, in order to locate the errors, I re-chain the west and north boundaries of the Tp., as follows:

Commencing at the closing corner, at which I set post, the SW. cor. of Tp. 23 S., R. 2 W., Thence I run, North bet. secs. 31 and 36

Va. 20*E.

Through timber. Ascend about 800 ft.

29.24 Find the 1/4 sec. cor., a post 4 ins. square, firmly set in the ground, marked 1/4 S. on W. face, from which, A double Fir, 70 ins. diam., bears North, 8 lks. dist., marked 1/4 S B T. A Fir, 36 ins. diam., bears S.10*E., 59 lks. dist. marked 1/4 S B T.

60.00 Summit of ridge, course SW. and descend about 80 ft. to

68.94 The cor. secs. 25, 30, 31 and 36, which is a post, 4 ft. long and 4 ins. square, firmly set in the ground, marked T 23 S S 30 on NE., R 2 W S 31 on SE.

R 3 W S 36 on SW and S 25 on NW. faces, with 5 notches on N. and 1 notch on S. edge, from which,

A Hemlock, 20 ins. diam., bears N.15*E., 66 lks. dist., marked T 23 S R 2 W S 30 B.T.

A Spruce, 40 ins. diam., bears S.80*E., 13 lks. dist., marked T 23 S R 2 W S 31 B T.

A Hemlock, --- ins. diam., bears S.85*W., 16 lks. dist., marked T 23 S R 3 W S 36 B T.

A Hemlock, 30 ins. diam., bears N.15*W., 39 lks. dist., marked T 23 S R 3 W S 25 B T.

I destroyed the marks referring to S. 30 and 31.

80.00 Set a Basalt stone 15 x 10 x 6 ins. --- ins. in the ground, for closing cor. to sec. 30 and 31, marked C C with 5 notches on N. and 1 notch on S. face, from which,

A Fir, 36 ins. diam., bears N.50*E., 37 lks. dist., marked T 23 S R 2 W S 30 B T.

A Fir, 16 ins. diam., bears S.40*E., 44 lks. dist.,