

## County Surveyor's Record, Douglas County, Oregon

- 20 -

Western Boundary of T. 23 S., R. 2 W., W.M.

CHAINS

marked T 23 S R 3 W S 24 B T.

I destroyed the marks referring to secs. 19 and 30.

80.00 Set a post 4 ft. long and 4 ins. sq., 24 ins. in the ground for closing cor. for sec. 19 and 30, marked C C T 23 S R 2 W on E., S 19 on N. and S 30 on S. faces, with 4 notches on N. and 2 notches on S. edges, from which

A Cedar, 24 ins. diam., bears N.56\*E., 40 lks. dist., marked T 23 S R 2 W S 19 B T.

A Cedar, 20 ins. diam., bears S.77\*E., 53 lks. dist., marked T 23 S R 2 W S 30 B T.

A Cedar, 10 ins. diam., bears S.44\*W., 5 lks. dist., marked T 23 S R 2 W C C S 19 and 30 B T.

Land, mountainous and heavily timbered Fir and Hemlock.

Dense undergrowth of Vine-maple and Hemlock.

Soil, sandy and rocky, 3rd and 4th rate.

80.00 chains

August 8, 1894.

Subdivisions of T. 23 S., R. 2 W., W.M.  
same Deputy and Contract.

Beginning at the cor. to secs. 35 and 36 on S. boundary of Township, Thence I run

N.0\*1'W., between secs. 35 and 36

Va. 20\*E.

Ascending through timber

27.00 Trail, from Oakland to Bohemia Mine on top of ridge bears E. and W.

Descend,

40.00 Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on W. face, from which,

A Fir, 8 ins. diam., bears East, 29 lks. dist., marked  $\frac{1}{4}$  S B T.

A Fir, 12 ins. diam., bears N.65\*W., 33 lks. dist.,

+200