

County Surveyor's Record, Douglas County, Oregon

-24-

Subdivisions of T. 23 S., R 2 W., W.M.

CHAINS		
	A Cedar, 36 ins. diam., bears N.61 ¹ / ₂ *W., 48 lks. dist., marked $\frac{1}{2}$ S B T.	
40.50	Ravine, course NE., ascend.	-200
61.00	Top of spur, course NE. Descend.	+ 75
63.00	Ravine, course N. Ascend.	50
79.60	To the cor. to secs. 23, 24, 25 and 26. Land, mountainous. Heavily timbered with Fir, Hemlock and scattering Cedar, Dense undergrowth of Vine-maple and Rhododendron. Soil, sandy and rocky; 3rd and 4th rate. 79.60 chains. August 13, 1894.	
	From the cor. to secs. 34 and 35 on S. boundary of Tp. I run, N.0*2'W. between secs. 34 and 35. Va. 20*E.	
	Ascending through timber.	
12.80	Creek, 3 lks. wide, course SW.	
30.00	Trail from Oakland to Bohemia Mines, bears NE. and SW.	
35.00	Top of ridge, bears E. and W. Descend	+400
40.00	Set basalt stone 12 x 12 x 6 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which, A Fir, 6 ins. diam., bears N.80*E., 9 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 10 ins. diam., bears N.36*W., 9 lks. dist., marked $\frac{1}{4}$ S B T.	
80.00	Set basalt stone 18 x 14 x 5 ins., 14 ins. in the ground, for cor. to secs. 26, 27, 34 and 35, marked with 1 notch on S. and 2 notches on E. edges, from which,	