

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 2 W., W.M.

CHAINS		
	A Hemlock, 18 ins. diam., bears S.8*W., 34 lks. dist., marked $\frac{1}{4}$ S B T.	
51.00	Top of spur, course N. Descend.	+100
68.75	Creek, 3 lks. wide, course NW. Ascend.	-400
71.50	Top of spur, course NW. Descend.	+50
72.50	Creek, 1 lk. wide, course NW. Ascend.	-40
80.40	To the cor. to secs. 21, 22, 27 and 28 Land, mountainous. Heavily timbered with Fir and Hemlock. Dense undergrowth of Vine-Maple. Soil, sandy and rocky; 3rd and 4th rate.  80.40 chains. August 22, 1894.	+60
	N.0*3'W., between secs. 32 and 33.  Va. 18*E.	
34.00	Ascending through timber Trail from Oakland to Bohemia mine, bears NW. and SE.	
40.00	On top of ridge, bears E. and W. Set basalt stone, 16 x 10 x 6 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which, A Fir, 26 ins. diam., bears S.48*E., 159 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 36 ins. diam., bears S.10*W., 148 lks. dist., marked $\frac{1}{4}$ S B T.	+500
76.50	Creek, 2 lks. wide, course NE.	-500
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 28, 29, 32 and 33, marked T 23 S S 28 on NE.; R 2 W S 33 on SE. S 32 on SW. and S29 on NW. faces, with 1 notch on S. and 4 notches on E. edges, from which	