

## County Surveyor's Record, Douglas County, Oregon

-34-

Subdivisions of T. 23 S., R. 2 W., W.M.

CHAINS		
40.00	On spur, course N. Descend. Set basalt stone 12x 10 x 8 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which, A Cedar, 24 ins. diam., bears N.81*E., 9 lks. dist., marked $\frac{1}{4}$ S B T. A Cedar, 18 ins. diam., bears S.20*E., 16 lks. dist., marked $\frac{1}{4}$ S B T.	+ 30
42.50	Creek, 4 lks. wide, course N. Ascend.	- 75
59.00	Top of spur, course N. Descend.	+200
77.50	Creek, 4 lks. wide, course NW. Ascend.	-300
80.15	To the cor. to secs. 28, 29, 32 and 33. Land, mountainous. Heavily timbered with Fir and Hemlock. Dense undergrowth of Vine-maple and Hemlock. Soil, sandy and rocky; 3rd and 4th rate. 80.15 chains.	+ 50
	N.0*3*W., between secs. 28 and 29 Va. 20*E. Descending through timber.	
6.50	Creek, 1 lk. wide, course E. Ascend.	- 70
22.00	Top of spur, course NE. Descend.	+250
38.75	Creek, 20 lks. wide, course W. Ascend.	-250
40.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which, A Hemlock, 14 ins. diam., bears S.74*E., 36 lks., dist., marked $\frac{1}{4}$ S B T. A Cedar, 40 ins. diam., bears S.31*W., 20 lks.	