

County Surveyor's Record, Douglas County, Oregon

- 35 -

Subdivisions of T. 23 S., R. 2 W., W.M.

CHAINS	dist., marked $\frac{1}{4}$ S B T.	
47.50	Creek, 1 lk. wide, course SE.	
80.00	Set basalt stone, 17 x 10 x 6 ins., 12 ins. in the ground, for cor. to secs. 20, 21, 28 and 29, marked with 2 notches on S. and 4 notches on E. edges, from which, A Fir, 12 ins. diam., bears N.48*E., 54 lks. dist., marked T 23 S R 2 W S 21 B T. A Chinquaspin, 6 ins. diam., bears S. 25*E., 18 lks. dist., marked T 23 S R 2 W S 28 B T. A Chinquapin, 6 ins. diam., bears S. 15*W., 29 lks. dist., marked T 23 S R 2 W S 29 B T. A Chinquapin, 6 ins. diam., bears N.70*W., 35 lks. dist., marked T 23 S R 2 W S 20 B T. Land, mountainous. Heavily timbered with Fir and Hemlock. Undergrowth of Vine-maple and Hemlock. Soil, sandy and rocky; 3rd and 4th rate. 80.00 chains	+500
	N. 89*54'E. on random line between secs. 21 and 28. Va. 20*E.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.	
80.20	Intersect N. and S. line, 13 lks. N. of cor. to secs. 21, 22, 27 and 28, Thence I run, West on true line between secs. 21 and 28. Va. 20*E. Descending through timber.	
8.40	Creek, 2 lks. wide, course NE. Ascend.	-250
30.50	Top of spur, course NW. Descend.	+ 50
38.00	Creek, 1 lk. wide, course NW. Ascend.	- 75
40.10	Set basalt stone, 12 x 10 x 6 ins., 9 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which,	