

South Boundary of T. 23^S; R. 3W., W. M.,
 as surveyed by James P. Currin, Deputy Surveyor, under Contract
 No. 438, dated May 2, 1882

CHAINS

Beginning at the established cor. to Tps. 23 & 24
 S. Rs. 3 & 4 W. which is a sandstone 12x8x6 ins. 8 ins.
 in the ground for cor. marked with 6 notches on each edge
 from which

A cedar, 36 ins. diam., bears N.1*E. 75 lks. dist.
 marked T 23 S R 3 W S 31 B T

A cedar, 30 ins. diam., bears S.30*E. 100 lks. dist.
 marked T 24 S R 3 W S 6 B T

A hemlock, 14 ins. diam., bears S.60*W. 37 ins. dist.
 marked T 24 S R 4 W S 1 B T

A fir, 46 ins. diam., bears N.30*W. 90 lks. dist.
 marked T 23 S R 4 W S 36 B T

East, on the S. boundary of Sec. 31.

Var. 17* 30' E.

Through dense forest of fir and hemlock

5.25 Creek 3 lks. wide flows S.

39.00 Creek 3 lks. wide flows S.

40.00 Set a post 4 ft. long 4 ins. sq. 24 ins. in the ground
 on S. slope in open timber for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on
 N. face from which

A maple, 4 ins. diam., bears S.25 lks. marked $\frac{1}{4}$ S.
 B T

A maple, 4 ins. diam., bears N.10*E. 35 lks. dist.
 marked $\frac{1}{4}$ S B T

66.80 Spring branch 3 lks. wide flows S.

80.00 Set a post 4 ft. long 4 ins. sq. 24 ins. in the ground
 for cor. to Secs. 5, 6, 31 & 32 marked with 5 notches
 on E. & 1 notch on W. faces from which

A dogwood, 7 ins. diam., bears N.35*E. 3 lks. dist.
 marked T 23 S R 3 W S 32 B T

A dogwood, 6 ins. diam., bears N.55*W. 50 lks. dist.
 marked T 23 S R 3 W S 31 B T

A yew, 12 ins. diam., bears S.55*W. 10 lks. dist.
 marked T 24 S R 3 W S 6 B T

A fir, 30 ins. diam., bears S.20*E. 3 lks. dist.