

County Surveyor's Record, Douglas County, Oregon

63

Subdivisional Lines of T. 23 S., R. 3 W.

CHAINS

Densely covered with forest of fir, hemlock & cedar.
timber 79.75 chs.

Thick fir & vine maple underbrush

North, on random line bet. secs. 7 & 8

Var. 18°15' E.

1.25 Stream 5 lks. wide flows E.

7.50 Stream 3 lks. wide flows NE.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

50.60 Stream 5 lks. wide flows NE.

72.00 Stream 1 lk. wide flows NE.

80.00 Intersect E. & W. line 1.35 chs. E. of cor. to Secs. 5,
6, 7 & 8 which is

A post firmly set in the ground marked

T 23 S S 5 on NE.

R 3 W S 8 on SE.

S 7 on the SW. and

S 6 on NW.

faces with 5 notches on S. and E. edges from which

A maple, 4 ins. diam., bears N.32°E. 29 lks. dist.

marked T 23 S R 3 W S 5 B T

A dogwood, 8 ins. diam., bears S.6°E. 81 lks. dist.

marked T 23 S R 3 W S 8 B T

A dogwood, 8 ins. diam., bears S.26°W. 69 lks. dist.

marked T 23 S R 3 W S 7 B T

A fir, 48 ins. diam., bears N.59°W. 71 lks. dist.

marked T 23 S R 3 W S 6 B T

Thence

S.0°58'E. On true line bet. secs. 7 & 8

Var.

40.00 Set a post 4 ft. long 4 ins. sq. 24 ins. in the ground
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face from which

A yew, 10 ins. diam., bears N.30°W. 42 lks. dist.

marked $\frac{1}{4}$ S B T

A fir, 28 ins. diam., bears N.80°E. 64 lks. dist.

marked $\frac{1}{4}$ S B T