

31
County Surveyor's Record, Douglas County, Oregon

2295

West Boundary of T. 23 S., R. 3 W.,
As surveyed by James P. Currin, Deputy, surveyor,
Under contract No. 438, Dated May 2, 1882

CHAINS

To survey the exterior lines of T.P.23 S., R. 3 W.,
I proceed as per-special instructions from the surveyor
General of Oregon to the established SW cor. of Sec. 7
Which I find to be a post firmly set in the ground
marked.

T 23 S S 7 on NE, R 3 W S 18 on SE, R 4 W S 13 on SW
and S 12 on NW faces with 2 notches on the N and 4
notches on S faces, from which

A cedar, 15 ins. diam., bears N.50*W., 45 lks. dist.

Marked T 23 S R 4 W S 12 B T

A cedar, 8 ins. diam., bears S.68*W., 37 lks. dist.

Marked T 23 S R 4 W S 13 B T

A cedar, 12 ins. diam., bears S.55*E., 12 lks. dist.

Marked T 23 S R 3 W S 18 B T

A fir, 80 ins. diam., bears N.50*E., 19 lks. dist.

Marked T 23 S R 3 W S 7 B T

From this corner I run S on W bdy. of sec. 18

Va. 18*30'E

10.00 Summit of Calipooia Mountains Course NW & SE

40.00 A fir, 50 ins. diam., which I mark $\frac{1}{4}$ on W face for $\frac{1}{4}$
Sec. cor., from which

A yew, 8 ins. diam., bears S.40*W., 25 lks. dist.

Marked $\frac{1}{4}$ S B T

A fir, 40 ins diam., bears N.10*E., 30 lks. dist.

Marked $\frac{1}{4}$ S B T

Cor. on E slope of mountain

60.00 Summit of Calipooia Mountains Course NE & SW plus 1000

78.50 Creek 5 lks. wide flows E

80.00 A vine maple 6 ins. diam., which I marked

T 23 S S 18 on NE, R 3 W S 19 on SE, R 4 W S 24 on SW
and S 13 on NW faces with 3 notches on N & S faces for
cor. to secs. 13, 18, 19 & 24, from which

A fir, 48 ins. diam., bears S.50*E., 12 lks. dist.

Marked T 23 S R 3 W S 19 B T