

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 4 W.,

CHAINS

S 34 on SW, S 27 on NW face, with 2 notches on E and
1 on S face, from which

A fir, 14 ins. diam., bears N.47*W., 35 lks. dist.

Marked T 23 S R 4 W S 27 B T

A fir, 12 ins. diam., bears N.28*E., 41 lks. dist.

Marked T 23 S R 4 W S 26 B T

A maple, 9 ins. diam., bears S.44*E., 38 lks. dist.

Marked T 23 S R 4 W S 35 B T

A maple, 8 ins. diam., bears S.82*W., 75 lks. dist.

Marked T 23 S R 4 W S 34 B T

Land, mountainous, rough

Soil, thin, poor

Timber, fir and cedar

Thick undergrowth of hazel 80 chs.

Knowing that it will be impossible to run this line
through between secs. 34 & 35, I run S on true line
between secs. 34 & 35

Va. $19\frac{1}{2}$ *E

Ascend 20*

4.50 Descend 27*

6.50 Ascend 40*

10.00 Top of ridge descend 35*

30.00 Elk creek flows SW, ascend 20*

37.00 Descend over ridge

40.00 Set post 4 ins. diam., 4 ft. long with marked stone 12 ins.
in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S in W face from
which

A fir, 50 ins. diam., bears N.24*W., 10 lka. dist.

Marked $\frac{1}{4}$ S B T

A fir, 24 ins. diam., bears S.47*W., 43 lks. dist.

Marked $\frac{1}{4}$ S B T

Ascend 20*