

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 4 W.,

CHAINS	
	<p>A fir, 36 ins. diam., bears N.5*W., 335 lks. dist. Marked T 23 S R 4 W, S 26 B T</p> <p>A fir, 36 ins. diam., bears N.19*E., 155 lks. dist. Marked T 23 S R 4 W, S 25 B T</p> <p>A fir, 48 ins. diam., bears S.75*W., 172 lks. dist. Marked T 23 S R 4 W, S 26 B T</p> <p>A fir, 6 ins. diam., bears S.49$\frac{1}{2}$*E., 112 lks. dist. Marked T 23 S R 4 W S 36 B T</p> <p>Land mountainous, very rough Soil, thin, poor & rocky Timber, mostly fir Thick undergrowth, hazel & Sallal 80 ohs.</p>
<p>40.00</p> <p>57.00</p>	<p>East, on random line between secs. 25 & 36 Va. 19$\frac{1}{2}$*E</p> <p>Set temp. $\frac{1}{4}$ sec. cor.</p> <p>Could go no further; the mountain too precipitus. Set a post 4 ins. diam., 4 ft. long with marked stone 12 ins. in ground for witness cor. to Sec. 25 & 36 marked T 23 S S 25 on N, W C on E and R 4 W S 36 on S face from which</p> <p>A fir, 4 ins. diam., bears N.20*E., 47 lks. dist. Marked T 23 S R 4 W, S 25 W C B T</p> <p>A fir, 4 ins. diam., bears S.67*W., 95 lks. dist. Marked T 23 S R 4 W, S 36 W C B T</p>
<p>17.00</p>	<p>Thence I run W in a true line between Sec. 25 & 36 Ascend 40* slope</p> <p>Set post 4 ins. diam., 4 ft. long, with marked stone 12 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face from which</p> <p>A fir, 40 ins. diam., bears N.8*W., 38 lks. dist. Marked $\frac{1}{4}$ S B T</p> <p>A fir, 48 ins. diam., bears S.50*E., 35 lks. dist.</p>