

## County Surveyor's Record, Douglas County, Oregon

## Sub-divisions of T. 23 S., R 4 W.,

CHAINS	
25.00	Top of ridge descend 15*
40.00	Set post 4 ins. diam. 4 ft. long with marked stone 12 ins. in ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on W face from which <p data-bbox="440 666 1398 762">A fir, 24 ins. diam., bears S.46*W., 28 lks. dist. marked <math>\frac{1}{4}</math> S B T</p> <p data-bbox="440 795 1398 891">A fir, 40 ins. diam., bears S.11*E., 55 lks. dist. marked <math>\frac{1}{4}</math> S B T</p>
80.00	Set post 6 ins. diam. 4 ft. long with marked stone 12 ins. in ground for cor. to sec. 7, 8, 17 & 18 marked T 23 S S 8 on NE, R 4 W S 17 on SE, S 18 on SW, S 7 on N W face with 5 notches on E and 4 in S edge from which <p data-bbox="435 1243 1393 1339">A fir, 40 ins. diam., bears N.16*W., 75 lks. dist. Marked T 23 S R 4 W, S 7 B T</p> <p data-bbox="435 1372 1393 1468">A fir, 70 ins. diam., bears S.36*E., 87 lks. dist. Marked T 23 S R 4 W, S 17 B T</p> <p data-bbox="435 1500 1393 1597">A fir, 10 ins. diam., bears N.78*E., 28 lks. dist. Marked T 23 S R 4 W, S 8 B T</p> <p data-bbox="435 1629 1372 1725">A fir, 5 ins. diam., bears S.43*W., 13 lks. dist. Marked T 23 S R 4 W, S 18 B T</p> <p data-bbox="334 1758 1047 1986">Land mountainous but not rough  Timber mostly fir but of poor quality  Soil thin and in places sickly  Thick undergrowth of hazel 80 chs.</p>
	East, on random line between Sec. 8 & 17 <p style="text-align: center;">Va. 23*E</p>
50.00	Set temp. $\frac{1}{4}$ Sec. cor
80.08	Intersect N & S line 30 lks. N of cor. to Sec. 8, 9, 16 and 17 which is a post 4 ins. diam. in ground marked T 23 S S 9 on NE, R 4 W S 16 on SE, S 17 on SW,