

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 23 S., R. 4 W.,

CHAINS	<p>This cor. is on a hillside, sloping E. Mag. decl.  19*30'E</p> <p>From this cor. I run West, on true line, on S bdy. of  sec. 36. Mag. decl. 19*30'E Ascend</p> <p>7.65 Top of ridge, bears N. and S, 100 ft. above closing cor.  Descend</p> <p>27.75 Muddy spring, 75 lks. wide, course N, 200 ft. below top  of ridge</p> <p>40.15 Set a yew post, 3 ft. long, 3 ins. sq., 24 ins. in the  ground, for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> S on N face, from  which</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears N.30*E., 15 lks.  dist. Marked <math>\frac{1}{4}</math> S B T</p> <p style="padding-left: 40px;">A yew, 8 ins. diam., bears S.27*E., 11 lks. dist.  Marked <math>\frac{1}{4}</math> S B T</p> <p>This cor. is on a hillside, sloping NW, 75 ft. below spring</p> <p>46.75 Creek, 2 lks. wide, course NW, 50 ft. below <math>\frac{1}{4}</math> sec. cor.</p> <p>56.63 Creek, 3 lks. wide, course S, 25 ft. below last creek,  Ascend spur.</p> <p>70.90 Top of spur, slopes S, 75 ft. above creek, descend</p> <p>80.15 Set a basalt stone, 12x8x8 ins., 8 ins. in the ground  for cor. of secs. 35, 36, 1 and 2 marked with 5  notches on W and 1 notch on E edges; from which</p> <p style="padding-left: 40px;">A chincapin, 12 ins. diam., bears N.8*E., 49 lks.  dist., Marked T 23 S R 4 W S 36 B T</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.58*E., 73 lks. dist.  Marked T 24 S R 4 W S 1 B T</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N.83*W., 59 lks. dist.  Marked T 23 S R 4 W S 35 B T</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S.28*W., 73 lks. dist.  Marked T 24 S R 4 W S 2 B T</p> <p>This cor. is in the bottom of ravine, 50 ft. below top  of spur.</p> <p>Land, mountainous</p> <p>Soil, 2nd, 3rd, and 4th rates</p> <p>Timber, scattering fir, cedar, hemlock, and chincapin</p>
--------	--