

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 4 W.

CHAINS	
2.13	Top of spur, slopes W, 25 ft. above closing cor; descend
4.68	Ravine, course W., 50 ft. below top of spur; ascend spur
7.38	Top of spur, slopes NW, 50 ft. above ravine; descend
21.13	Creek, 2 lks. wide, course NW 175 ft. below top of spur
21.38	To witness corner between sections 34 and 35
	Land, mountainous
	Soil, 3rd rate
	Timber, fir, cedar, hemlock, chincapin, and madrona
	Dense undergrowth of vine-maple, mountain-balm, ocean-spray and hazel.
	Land, mountainous, heavily timbered, or covered with dense undergrowth, 21.38 chs.
	From the cor. of secs. 25, 26, 35 and 36, which is a post, 4 ins. sq., 24 ins. above ground, marked and witnessed as described by the surveyor general, I run
	South $0^{\circ}1'E.$, on a random line between secs. 35 & 36
40.00	Set a temp. $\frac{1}{4}$ sec. cor.
80.40	Intersect E and W line, 30 lks. W of cor. of secs. 1, 2, 35 and 36 which I set July 16, 1897.
	Thence I run North, $14^{\circ}W.$, on true line, between secs. 35 and 36, ascend spur.
	Mag. Decl. $19^{\circ}30'E$
1.50	Top of spur, slopes SW 25 ft. above sec. cor., descend
2.90	Creek 1 lk. wide, course SW 25 ft. below spur, ascend spur.
40.40	Top of spur, sloping SW, 100 ft. above creek last noted
	Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face, from which
	A fir, 50 ins. diam., bears $S.34^{\circ}E.$, 9 lks. dist.
	Marked $\frac{1}{4}$ S B T
	A fir, 36 ins. diam., bears $N.35^{\circ}W.$, 9 lks. dist.
	Marked $\frac{1}{4}$ S B T
	Descend